



# Telair Actuator 880T100-3



Choose Derco and Telair for a price that can't be beat and support that can't be matched . . .

**Superior Distribution:**

All parts are in Factory New condition. No one stocks more Telair parts and components.

**Repair capability:**

Derco stocks 100% replacement parts and guarantees repairs in 30 days or less.

**Pricing:**

Derco will beat or match all manufacturer's authorized sources' pricing.

## Superior Distribution

- Derco commits more than 60% of its Telair inventory to the support of the 880 actuator—allowing for quick turn around on spare parts.
- All parts are in Factory New condition

## Repair Capability

- Derco stocks 100% replacement parts and guarantees repairs in 30 days or less

## Pricing

- Volume discounts allow Derco to offer the best pricing in the market

## Stability

**Telair Actuation** is a world leader in aftermarket service and support for commercial and military aircraft actuators, serving all major OEMs and airlines. Telair's operations in Simi Valley, California, boasts of one of the most experienced and talented staffs in the industry, and it includes technical support directly from factory engineers. Teleflex actuators are found around the world in applications ranging from slat and flap systems to stabilizer drives, boundary layer control systems, and more.

**Derco Aerospace** is the exclusive distributor for Telair International. Telair products support a wide variety of aircraft including the C-130 and F-16. Components include, but are not limited to, pumps, fuel flow dividers, canopy and linear actuators, valves, winches and a wide range of associated piece parts.

## 880T100-3 C-130 Features

- Lockheed approved spare
- Fully interchangeable with base PNs: 8656 (CEF) and 1105123 (Smiths)
- Applicable to the C-130J model
- Integral EMI filter
- Overload protection provided by a friction clutch
- Contains adjustable stroke limit switches and mechanical stops in the event of a switch failure.
- Units are 100% sealed for oil intrusion protection
- 12 month warranty
- NSN: 1680-01-329-7411

## 880T100-3 C-130 Specifications

Voltage	V26 VDC
Rated Current	7 Amperes
Stall Current	14 Amperes
Stroke	4.55 inches
Rated Load (Extend)	200 pounds
Rated Load (Retract)	500 pounds
Maximum Load	1000 pounds
Operating Time	15 seconds
Altitude	0 to 60,000 feet
Duty Cycle	3 mins. ON, 17 mins. Off
Duty Life	10,000 cycles
Weight	5 lbs 5 ounces

